

Care & Maintenance



Terralon/Terralon Smooth/Terralon Regatta

GENERAL CLEANING, REMOVING DAY-TO-DAY SOIL

Ordinary dirt and smudges can be removed with a mild soap and warm water. Clean from bottom of wall upward. Rinse thoroughly with clean water from the top down using a sponge. Deeply embossed wallcoverings need extra attention to remove suds or loosened dirt that may lodge in the embossing. Dry wallcovering with a soft lint free cloth or towel.

All stains should be attempted to be removed with soap and water first. Iso-propyl alcohol may set some stains that soap and water may remove.

For more difficult stains that are only surface deep, the use of a stronger detergent is recommended. Always test an inconspicuous area with the stronger detergent to be sure that the surface and ink are not damaged.

DO NOT USE steel wool, powdered abrasive or abrasive materials/sponges because they can damage the image and textured surface and leave unsightly appearance.

DO NOT USE solvents, alcohol, pine oil, or cleaners that contain these kinds of products as they can remove the image and damage the textured surface.

When cleaning, always take measures to prevent water from dripping behind molding.

NEVER MIX CLEANING AGENTS TOGETHER, VIOLENT REACTIONS MAY OCCUR.

ADDITIONAL SURFACE PROTECTION

For added protection against scratch, abrasion and mildew we recommend applying DreamGuard Protex 3. DreamGuard Protex 3 is a water based, nonhazardous liquid topcoat specially formulated to resist mold and mildew growth and protect against surface scratches and abrasion. DreamGuard is easily applied with a common ¼" nap paint roller and dries to a clear finish. DreamGuard Protex 3 is available in two finishes-satin and matte.