Specification





Application

Walls, for indoor use in environmentally controlled spaces

Ground

Terralon Smooth™, sustainable, PVC-Free, Breathable, Eco-Friendly

Characteristics

CONTENT: Proprietary Polyester/Natural Fibers

BACKING: Non-Woven PET

WIDTH: 51"

REPEAT: 48" V, 51" H

HANGING INSTRUCTIONS: Straight match

WEIGHT: 12 oz/lineal yd

Performance

FLAMMABILITY: ASTM-E84 Tunnel Test, Class A

CAN/ULC-S102.2 Passed all requirements

ENVIRONMENTAL: PVC & POA (Olefin) free, no plasticizers, no chlorine, no formaldehyde, no heavy metals

NSF-342 - Certified Silver compliance Eligible for LEED v4 contribution Phthalate free formulation Prop 65 compliant

EU Toxicity - meets all requirements

Manufactured without the use of Brominated flame retardants

Recycled content - minimum 31% post-consumer recycled content

MOLD/MILDEW: ASTM-G21 Specifications, passed all requirements

INDOOR AIR QUALITY: Low VOC, meets California CDPH Standard for Schools and Offices

Tested per CA 01350

LEED: Terralon Smooth™ can contribute towards the earning of up to 7 LEED Credits

MR Credit 4.1 Recycled content 10% MR Credit 4.2 Recycled content 20% Conditionally- MR Credit 2.1, 2.2, 5.1

Conditionally- EQ Credit 4.1 (when mounted with use of low emitting adhesives), 4.6

WARRANTY: 3 years against manufacturing defects

Specification













19-20 Black+White+Gray ECO 19-20 Black+White+Gray ECO 19-21 Dolphin ECO

19-22 Sand ECO

Additional Colorways Available on other substrates

Metallic